



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04J 3/06	A1	(11) International Publication Number: WO 97/37451
		(43) International Publication Date: 9 October 1997 (09.10.97)
(21) International Application Number: PCT/US97/04818		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 25 March 1997 (25.03.97)		
(30) Priority Data: 08/625,716 29 March 1996 (29.03.96) US		
(71) Applicant: DSC COMMUNICATIONS CORPORATION [US/US]; 1000 Coit Road, Plano, TX 75075 (US).		
(72) Inventors: ROBERTS, Martin; 18B The Green, Deanshanger, Milton Keynes MK19 6HL (GB). POTTER, Thomas, A.; 1437 Sarkesian Drive, Petaluma, CA 94954 (US).		
(74) Agent: FISH, Charles, S.; Baker & Botts, L.L.P., 2001 Ross Avenue, Dallas, TX 75201-2980 (US).		

Published


With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: MULTI-RATE TRANSMISSION SYSTEM

(57) Abstract

A multi-rate transmission system (10) includes a receive section (12) and a transmit section (14). The receive section includes a receiver (16), a clock recovery unit (18), and a serial to parallel converter (20) all operating at a first clock rate (M). The receiver (16) also has a frame recovery unit (22) that operates at any of a plurality of clock rates, including the first clock rate (M) and a second clock rate (M/n). When the frame recovery unit operates at the first clock rate (M), frame information received by the receiver section (12) has unique bits occupying each bit position associated with each clock pulse of the first clock rate (M). When the frame recovery unit (22) operates at the second clock rate (M/n), each unique bit of the frame information occupies a number of bit positions according to a ratio of the first clock rate (M) to the second clock rate (M/n). Similar operation occurs with respect to a frame formatter (30) in the transmit section (14) of the multi-rate transmission system (10).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Larvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

MULTI-RATE TRANSMISSION SYSTEM

TECHNICAL FIELD OF THE INVENTION

The present invention relates in general to a telecommunications environment and more particularly to a multi-rate transmission system.

5

BACKGROUND OF THE INVENTION

Many modern transmission products, such as SONET fiber optic transmission systems, are required to have variants in order to operate at different clock rates. Development of these products becomes unnecessarily complicated and time consuming because one set of components is required for one clock rate and another set of components is required for another clock rate. Upgrading the transmission system or changing the clock rate requires disposal and replacement of a large number of components, significantly increasing the cost and design cycle time of the system. Further, changes in system clock rates cannot be performed remotely, requiring the system to suffer down time in order to affect the changes. Therefore, it is desirable to have a transmission system that can perform in response to changes in clock rates without adversely affecting performance and development.

10

15

20

SUMMARY OF THE INVENTION

25

From the foregoing, it may be appreciated that a need has arisen for a transmission system that provides multi-rate operation. In accordance with the present invention,

a multi-rate transmission system is provided that substantially eliminates or reduces disadvantages and problems associated with conventional fixed rate transmission systems.

5 According to an embodiment of the present invention, there is provided a multi-rate transmission system that includes a receiver capable of receiving a serial data stream. The serial data stream has a first clock rate. A clock recovery unit generates a first clock signal with the
10 first clock rate in response to the serial data stream. A serial to data converter converts the serial data stream into a parallel format in response to the first clock signal. A frame recovery unit places the parallel format into a frame format. The frame recovery unit is capable of
15 operating at any of a plurality of clock rates to include the first clock rate. With the frame recovery unit operating at the first clock rate, the serial data stream is made up of a plurality of consecutive unique bits. With the frame recovery unit operating at a second clock rate
20 that is an integer value fraction of the first clock rate, the serial data stream is made up of unique bits wherein each unique bit occupies a number of consecutive bit positions equal to the integer value in order to provide multi-rate operation.

25 The present invention provides various technical advantages over conventional fixed rate transmission systems. For example, the multi-rate transmission system can operate with any of a plurality of clock rates. Another technical advantage is that unique bits can be
30 repeated to adjust for differences in clock rates between system components. Yet another technical advantage is the ability to remotely change the operating clock rate without swapping out system components. Other technical advantages

are readily apparent to one skilled in the art from the following figures, description, and claims.

BRIEF DESCRIPTION OF THE DRAWINGS

5 For a more complete understanding of the present invention and the advantages thereof, reference is now made to the following description taken in conjunction with the accompanying drawings, wherein like reference numerals represent like parts, in which:

10 FIGURE 1 illustrates a simplified block diagram of a multi-rate transmission system;

FIGURE 2 illustrates a bit sequence of a receive side of the multi-rate transmission system at a first clock rate;

15 FIGURE 3 illustrates a bit sequence of the receive side of the multi-rate transmission system at a second clock rate; and

FIGURE 4 illustrates a bit sequence of a transmit side of the multi-rate transmission system at the second clock rate.
20

DETAILED DESCRIPTION OF THE INVENTION

FIGURE 1 is a simplified block diagram of a multi-rate transmission system 10. Multi-rate transmission system 10 includes a receive section 12 and a transmit section 14. Receive section 12 includes a receiver 16, a clock recovery unit 18, and a serial to parallel converter 20 operating at a first clock rate M. Receiver section 12 also has a frame recovery unit 22 operating at any one of a plurality of clock rates, including first clock rate M and a second clock rate M/n. Transmitter section 14 includes a transmitter 24, an oscillator 26, and a parallel to serial converter 28 operating at first clock rate M. Transmitter 14 also has a frame formatter 30 operating at any one of a
25
30

plurality of clock rates, including first clock rate M and second clock rate M/n .

5 In operation, a serial data stream is provided to receiver 16 of receiver section 12 from a transmission medium 32. Transmission medium 32 may be any conventional carrier of telecommunications information to include a fiber optic communication path. Clock recovery unit 18 generates a receive clock signal having first clock rate M in response to the serial data stream received by receiver 10 16. Serial to parallel converter 20 converts the serial data stream into a parallel format in response to the receive clock signal generated by clock recovery unit 18. Frame recovery unit 22 identifies the frame information transferred by the serial data stream for further processing by telecommunication components in communication 15 with receiver section 12.

FIGURE 2 shows a bit sequence of the serial data stream for frame recovery unit 22 operating at first clock rate M . Each bit position of the serial data stream has a 20 unique bit associated therewith at each clock pulse of the frame information transported from transmission medium 32. Frame recovery unit 22 selects every bit position of the received data in order to properly interpret the data for appropriate processing.

25 FIGURE 3 shows a bit sequence of the serial data stream for frame recovery unit 22 operating at second clock rate M/n , where n is equal to 4. Each unique bit of the frame information occupies a number of bit positions corresponding to first clock rate M associated with an integer value ratio between first clock rate M and second 30 clock rate M/n . For the example shown, each unique bit of the frame information occupies four bit positions of first clock rate M . Frame recovery unit 22 receives data at first clock rate M with each unique bit spanning four clock

pulses of first clock rate M. Frame recovery unit 22 continues to operate at first clock rate M, but selects every fourth bit position of the received data in order to correctly interpret the data. Frame recovery unit 22
5 arbitrarily selects the every fourth bit position sequence. Though frame recovery unit 22 does not know where the boundaries are for each bit position, arbitrary selection will result in recovery of a valid bit sequence.

For operation of transmit section 14, frame formatter
10 30 receives unframed data from processing components in communication with transmit section 14 and provides the appropriate overhead and data manipulation according to the clock rate desired for proper transmission of frame
15 information. Frame formatter 30 generates a parallel format from the frame information that is converted into a serial data stream by parallel to serial converter 28. Oscillator 26 generates a transmit clock signal having
20 first clock rate M to drive parallel to serial converter 28. Transmitter 24 places the serial data stream onto transmission medium 32 at first clock rate M.

For operation at first clock rate M, frame formatter
30 processes the frame information such that a unique bit is present at each bit position of the serial data stream for each clock pulse of first clock rate M as shown in
25 FIGURE 2.

FIGURE 4 shows a bit sequence of the serial data
stream for frame formatter 30 operating at second clock
rate M/n , where n is equal to 4. Each unique bit of the
frame information is repeated a number of times associated
30 with the integer value ratio between first clock rate M and second clock rate M/n . For the example shown, four repeats of each unique bit of the frame information are performed by frame formatter 30. This allows for frame formatter 30 to provide data on transmission medium 32 at the slower

second clock rate M/n through the components of transmit section 14 operate at the faster first clock rate M .

5 Frame information can be transported at a maximum clock rate or at any integer value fraction of the maximum clock rate in the telecommunications environment. The clock rate for multi-rate transmission system 10 can be changed through software modifications without replacing all the components of multi-rate transmission system 10.

10 In summary, a multi-rate transmission system can operate at a plurality of rates by having the majority of components operating at a fixed first clock rate and a single multi-rate component on both the receive and transmit side operating at any of a plurality of clock rates. Unique bits occupy each bit position of a serial
15 data stream when all components operate at the first clock rate. Unique bits are repeated into a number of bit positions in the serial data stream when the single multi-rate component of both the receive and transmit side operates at a second clock rate which is an integer
20 fraction of the fixed first clock rate.

Thus, it is apparent that there has been provided in accordance with the present invention, a multi-rate transmission system that satisfies the advantages set forth above. Although the present invention has been described
25 in detail, it should be understood that various changes, substitutions, and alterations readily ascertainable to one skilled in the art can be made herein without departing from the spirit and scope of the present invention as defined by the following claims.

WHAT IS CLAIMED IS:

1. A multi-rate transmission system, comprising:
 - a receiver operable to receive a serial data stream, the serial data stream having a first clock rate;
 - 5 a clock recovery unit operable to generate a first clock signal having the first clock rate;
 - a serial to parallel converter operable to convert the serial data stream into a parallel format in response to the first clock signal;
 - 10 a frame recovery unit operable to recover frame information from the parallel format, the frame recovery unit operating at any of a plurality of clock rates including the first clock rate.
- 15 2. The multi-rate transmission system of Claim 1, wherein the frame recovery unit operates at the first clock rate, the serial data stream being comprised of unique bits at each clock pulse of the first clock rate.
- 20 3. The multi-rate transmission system of Claim 1, wherein the frame recovery unit operates at a second clock rate, the second clock rate being an integer value fraction of the first clock rate.
- 25 4. The multi-rate transmission system of Claim 3, wherein the serial data stream has a plurality of unique bits, each unique bit being repeated in a number of bit positions, wherein the number equals the integer value.
- 30 5. The multi-rate transmission system of Claim 4, wherein the frame recovery unit selects every nth bit of the serial data stream according to the second clock rate.

6. A multi-rate transmission system, comprising:
a clock oscillator operable to generate a clock signal
at a first clock rate;
a frame formatter operable to process frame
5 information into a parallel format, the frame formatter
operating at any of a plurality of clock rates including
the first clock rate;
a parallel to serial converter operable to convert the
parallel format into a serial data stream, the parallel to
10 serial converter operating at the first clock rate
generated by the clock oscillator;
a transmitter operable to send the serial data stream,
the transmitter operating at the first clock rate.
- 15 7. The multi-rate transmission system of Claim 6,
wherein the frame formatter operates at the first clock
rate, each bit position of the frame information
corresponding to a clock pulse of the first clock rate
having a unique bit.
- 20 8. The multi-rate transmission system of Claim 6,
wherein the frame formatter operates at a second clock
rate, the second clock rate being an integer value fraction
of the first clock rate.
- 25 9. The multi-rate transmission system of Claim 8,
wherein the frame information has a plurality of unique
bits, the frame formatter repeating each unique bit a
number of times equal to the integer value.
- 30

10. The multi-rate transmission system of Claim 9, wherein the serial data stream includes the plurality of unique bits, each unique bit occupying consecutive bit positions of the serial data stream according to the integer value.

5




FIG. 1

2/2




FIG. 2




FIG. 3




FIG. 4

INTERNATIONAL SEARCH REPORT

Intern. Application No
PCT/US 97/04818A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H04J3/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 H04L H04J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 827 477 A (AVANEAS NAPOLEON G) 2 May 1989 see abstract see column 1, line 41 - column 2, line 8 see column 3, line 30 - line 58 see column 4, line 52 - column 7, line 9 see column 12, line 40 - line 43 ---	1-10
X	EP 0 535 768 A (DSC COMMUNICATIONS) 7 April 1993 see column 1, line 3 - column 2, line 26 see column 2, line 54 - column 4, line 35 ---	1,2
A	---	3
X	EP 0 346 896 A (FUJITSU LTD) 20 December 1989 see column 1, line 3 - line 52 see column 2, line 15 - line 37 see column 3, line 32 - column 7, line 2 ---	6-8
	--- -/-	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *&* document member of the same patent family

Date of the actual completion of the international search

2 July 1997

Date of mailing of the international search report

25.07.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+ 31-70) 340-3016

Authorized officer

Chauvet, C

INTERNATIONAL SEARCH REPORT

Intern: I Application No

PCT/US 97/04818

C (Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 445 215 A (SVENDSEN GORDON D) 24 April 1984 see abstract -----	6,8

1

INTERNATIONAL SEARCH REPORT

Information on patent family members

Intern. Application No

PCT/US 97/04818

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4827477 A	02-05-89	NONE	
EP 0535768 A	07-04-93	US 5253254 A AU 654210 B AU 2523092 A JP 7202865 A	12-10-93 27-10-94 25-03-93 04-08-95
EP 0346896 A	20-12-89	JP 1317026 A JP 7073219 B CA 1304845 A DE 68911761 D DE 68911761 T US 4965797 A	21-12-89 02-08-95 07-07-92 10-02-94 09-06-94 23-10-90
US 4445215 A	24-04-84	DE 3307781 A FR 2522905 A GB 2119137 A,B JP 6054875 B JP 58164319 A	15-09-83 09-09-83 09-11-83 20-07-94 29-09-83